

# LIFT / BUNDLING SCHEDULE

Sched. 40 - Std Wt.

Welded Steel Pipe

NPS	NOM. WALL TKS.	WT. PER FT.	PCS. PER BDLE.	BDLES. PER LIFT	PCS. PER LIFT	21 Feet		24 Feet	
						FEET PER LIFT	WT/LBS PER LIFT	FEET PER LIFT	WT/LBS PER LIFT
1/8	.068	.2447	35	12	420	8820	2158		
1/4	.088	.4248	20	12	240	5040	2141		
3/8	.091	.5676	15	12	180	3780	2146		
1/2	.109	.8510	12	10	120	2520	2145		
3/4	.113	1.131	7	12	84	1764	1995		
1	.133	1.679	5	12	60	1260	2116	1440	2418
1-1/4	.140	2.273	3	14	42	882	2005	1008	2291
1-1/2	.145	2.718	3	12	36	756	2055	864	2348
2	.154	3.653			26	546	1995	624	2280
2-1/2	.203	5.793			18	378	2190	432	2503
3	.216	7.576			14	294	2227	336	2546
3-1/2	.226	9.109			11	231	2104	264	2405
4	.237	10.79			10	210	2266	240	2590
5	.258	14.62			8	168	2456	192	2807
6	.280	18.97			7	147	2789	168	3187
8	.322	28.55			5	105	2998	120	3426

## LiteWall - (Schedule 10) Welded Steel Pipe

1-1/2	.109	2.085			36	756	1576	864	1801
2	.109	2.638			26	546	1440	624	1646
2-1/2	.120	3.531			18	378	1335	432	1525
3	.120	4.332			14	294	1274	336	1456
3-1/2	.120	4.973			12	252	1253	288	1432
4	.120	5.613			19	399	2240	456	2560
5	.134	7.770			10	210	1632	240	1865
6	.134	9.289			10	210	1951	240	2230
8	.188	16.94			5	105	1779	120	2033

## BS 1387 Steel Tubes & Tubular Lite

OUTSIDE DIA.	PC PER LIFT	WT. PER FT.	NOM. WALL	21 Feet		24 Feet		
				FEET PER LIFT	WT/LBS PER LIFT	FEET PER LIFT	WT/LBS PER LIFT	
1-3/8	1.328	91	1.345	104	1911	2570	2184	2938
1-5/8	1.670	61	1.73	104	1281	2216	1464	2533
1-7/8	1.903	61	2.205	116	1281	2825	1464	3228
2-3/8	2.370	37	2.76	116	777	2145	888	2451
2-7/8	2.991	19	3.748	128	399	1496	456	1709

## BSS 1387 Lite Wall GPE Fence Tubing

NOM. OUTSIDE DIA.	NOM. BORE SIZE	NOM. WALL TKS.	WT. PER FT.	PCS. PER LIFT	18 Feet		21 Feet		24 Feet	
					FEET PER LIFT	WT/LBS PER LIFT	FEET PER LIFT	WT/LBS PER LIFT	FEET PER LIFT	WT/LBS PER LIFT
1-3/8 or 1.315	1"	.104	1.345	91	1638	2203	1911	2570	2184	2937
1-5/8 or 1.660	1-1/4"	.104	1.728	61	1098	1897	1281	2214	1464	2530
1-7/8 or 1.900	1-1/2"	.116	2.205	61	1098	2421	1281	2825	1464	3228
2-3/8 or 2.375	2"	.116	2.800	37	666	1865	777	2176	888	2486
2-7/8 or 2.875	2-1/2"	.128	3.748	19	342	1282	399	1495	456	1709

## .069 Fence Tubing GPE

NOM. OUTSIDE DIA.	NOM. BORE SIZE	NOM. WALL TKS.	WT. PER FT.	PCS. PER LIFT	18 Feet		21 Feet		24 Feet	
					FEET PER LIFT	WT/LBS PER LIFT	FEET PER LIFT	WT/LBS PER LIFT	FEET PER LIFT	WT/LBS PER LIFT
1-3/8 or 1.315	1"	.069	.919	91	1638	1505	1911	1756	2184	2007
1-5/8 or 1.660	1-1/4"	.069	1.173	61	1098	1288	1281	1503	1464	1717
1-7/8 or 1.900	1-1/2"	.069	1.349	61	1098	1481	1281	1728	1464	1975
2-3/8 or 2.375	2"	.069	1.670	37	666	1112	777	1298	888	1483

## TRUCK LOADING SCHEDULE FOR BARE STEEL PIPE

### Number of pieces per layer

NPS O.D.	Plain Ends	Max. Layers (102")	NPS O.D.	Plain Ends	Max. Layers (102")
3"	31	18	12-3/4"	7	7
3-1/2"	27	22	14"	6	7
4"	23	20	16"	6	6
4-1/2"	21	18	18"	5	5
5"	19	17	20"	4	4/3**
6"	16	14	24"	4	4
6-5/8"	14	13	26"	3	3/2**
7"	13	12	28"	3	3/2
8"	12	11	30"	3	3
8-5/8"	11	10	32"	3	3
10"	9	9	34"	2	2/1**
10-3/4"	8	8	36"	2	2/1**
12"	8	7			

NOTE - 1" Dunnage used between layers of pipe

\*\*Cradled at top